

HOLEX®
Micrometer with dial comparator, Measuring range: 0-25 mm

Order data

Order number	422510 0-25
GTIN	4045197203991
Item class	42B

Description
Version:

Measuring spindle through hardened and ground.
 With precision lapped **carbide tipped anvils**.
 Spindle and anvil of stainless steel.
 One piece frame and spindle guide.
 Button for retracting the measurement anvil for repetitive measurements.
 With adjustment screw for zeroing.
 Tolerance pointers for good/ reject measurements.
 With hand temperature protection. Lever for spindle clamping.

Callout:

Deviation read-off in 1/1000 mm.
 Push button for anvil retraction.

Accuracy:

Dial comparator 1 µm – micrometer 3 µm.

Supplied with:

Adjustment wrench.
 Norm: DIN 863
 Micrometer barrel graduations: 1/50 mm
 Packaging: sturdy box
 Calibration: B9
 Measuring range dial comparator: ±0.045 mm
 Graduation of the micrometer: 0.01 mm
 Graduation of the precision dial comparator: 0.001 mm
 Clearance depth of micrometer frame: 18 mm

Technical description

Measuring range dial comparator	±0.045 mm
Graduation of the micrometer	0.01 mm
Graduation of the precision dial comparator	0.001 mm
Measuring range	0 - 25 mm
Clearance depth of micrometer frame	18 mm
Norm	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B9

Services

Calibration Indicator micrometer maximum measuring range 25 mm	012240 25
Labelling laser-etched	018940